

| REV | REV DATE | DESCRIPTION |  |  |  |  |  |  |  |  |  |  |
|-----|----------|-------------|--|--|--|--|--|--|--|--|--|--|
|     |          |             |  |  |  |  |  |  |  |  |  |  |

X GÖRÜNÜŞÜ

| Kod / Code | İletim Hacmi<br>Displacement | Maksimum Hız<br>Maximum speed (RPM) |      | Torque<br>Tork (m.N) |             | A    | B    | C       | E     | F     | G    |                                                         |  |           |  |
|------------|------------------------------|-------------------------------------|------|----------------------|-------------|------|------|---------|-------|-------|------|---------------------------------------------------------|--|-----------|--|
|            | (cm³ /rev)                   | Nom                                 | Max  | 350 ( Bar )          | 400 ( Bar ) | (mm) | (mm) | (inch)  | (mm)  | (mm)  | (mm) |                                                         |  |           |  |
| AM023SF131 | 23                           | 6300                                | 6900 | 140                  | 160         | 180  | 58   | G3/4"   | 89    | 89    | 52   |                                                         |  |           |  |
| AM032SF131 | 32                           | 6300                                | 6900 | 175                  | 200         | 180  | 58   |         |       |       |      |                                                         |  |           |  |
| AM045SF131 | 45                           | 5600                                | 6200 | 227                  | 260         | 210  | 78   | G1"     | 108,7 | 108,7 | 59   | Tapaların Sıkma Torku<br>Tightening Torque Of The Plugs |  |           |  |
| AM056SF131 | 56                           | 5000                                | 5500 | 280                  | 320         | 218  | 80   |         | 110,5 | 108   | 64   | G1/2"                                                   |  | 55-65Nm   |  |
| AM063SF131 | 63                           | 5000                                | 5500 | 350                  | 400         |      |      |         | 110,5 | 108   | 64   | G3/4"                                                   |  | 90-100Nm  |  |
| AM080SF131 | 80                           | 4500                                | 5000 | 445                  | 508         | 245  | 94   | G1 1/4" | 127   | 118   | 69   | G1"                                                     |  | 135-160Nm |  |
| AM107SF131 | 107                          | 4000                                | 4400 | 595                  | 680         | 255  |      |         | 131,6 | 130   | 77   | G1 1/4"                                                 |  | 200-230Nm |  |
| AM125SF131 | 125                          | 3400                                | 4400 | 700                  | 800         |      |      |         | 131,6 | 130   | 77   |                                                         |  |           |  |

| ANMA ÇAPI |  | Quality of screw<br>12.9 |          |
|-----------|--|--------------------------|----------|
|           |  | Kgm                      | Nm -Tork |
| M12x1.75  |  | 14.57                    | 143      |

|          |     |                                    |            |           |  |
|----------|-----|------------------------------------|------------|-----------|--|
|          |     | NAME-SURNAME                       | DATE       | SİGNATURE |  |
| DRAWER   |     | A.AKGÖZ                            | 14.07.2026 |           |  |
| CONTROL  |     | M.KAZEL                            | 14.07.2026 |           |  |
| APPROVAL |     | M.KAZEL                            | 14.07.2026 |           |  |
| SCALE    | 1:2 | PRODUCT NAME:ISO FEYZ PISTON MOTOR |            |           |  |